



DORIS L662W95 PCO HF 840 LO
WATERPROOF LUMINAIRES

90617L060E00000



Light distribution



L=662mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted, Suspended, Wall mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

DORIS L662W95 PCO HF 840 LO

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 66
Mechanical Impact Protection (IK): 10
Ambient Temperature Range (°C):]-25°C, 40°C[
Warranty (Years): 5
Current Supply Cable Entry Point: End cap

MATERIALS

Body Material: Injected polycarbonate
Finishing: Epoxy polyester powder coated
Glow-wire Resistance (°C): 850

OPTICAL SYSTEM

Optical System: PCO - Opal Diffuser
Light Distribution: Direct
Beam Angle (°): 150

TECHNICAL DATA

Light Source: LED

Input Power (W): 14
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,95
Luminaire Luminous Flux (lm): 1958
Luminaire Efficacy (lm/W): 140
Unified Glare Rating (UGR): <28
LED Lifetime - Rated Median Useful Life: 50.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): 80
LED Module Forward Voltage Range (VF): 39,9
Power Supply Dimming: ON/OFF
Central Battery Emergency Lighting System (VDC): 170-276
Maximum of Luminaires by Magnetic Circuit Breaker B16: <50
Inrush Current (A): 5
Pulse Duration (µs): 50

DIMENSIONS

L - Length (mm): 662
W - Width (mm): 95
H - Height (mm): 111
Net Weight (kg): 1.3