


ROFY 85 D/I D0600 GCONTROL+ HF K3 840 I HO
ARCHITECTURAL LIGHTING

90624L600EI3000



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Suspended
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 85 D/I D0600 GCONTROL+ HF K3 840 I HO

CHARACTERISTICS

Luminaire Type: Circular luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 40
Mechanical Impact Protection (IK): 4
Ambient Temperature Range (°C):]5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Steel sheet
Frame Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Carbon (I)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: gCONTROL+ - Microprismatic diffuser
Light Distribution: Direct / Indirect
Beam Angle (°): 96

TECHNICAL DATA

Light Source: LED
Input Power (W): 56
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,92
Luminaire Luminous Flux (lm): 7494
Luminaire Efficacy (lm/W): 134
Emergency Unit: 3
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: B
LED Module Forward Voltage Range (VF): 95,2
Power Supply Dimming: ON/OFF
Maximum of Luminaires by Magnetic Circuit Breaker B16: <26
Inrush Current (A): 39
Pulse Duration (µs): 166
This Product contains a Light Source of Energy Efficiency Class [Indirect]: C

DIMENSIONS

H - Height (mm): 85
D - Diameter (mm): 600

NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately;
- In order to guarantee a total uniformity of light on the ceiling, the installation must be done at a minimum distance of 500 mm.