




ZLP /E L1225W300 DOZ DALI 840 W
VANDAL RESISTANT LUMINAIRES

906J2222JE40000



Light distribution



L=1225mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Recessed
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

ZLP /E L1225W300 DOZ DALI 840 W

CHARACTERISTICS

Luminaire Type: Rectangular luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 65
Mechanical Impact Protection (IK): 10
Ambient Temperature Range (°C):]-5, 25[
Fixing System: Brackets
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Steel sheet
Frame Material: Steel sheet
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 850

OPTICAL SYSTEM

Optical System: DOZ - Opal diffuser
Light Distribution: Direct
Beam Angle (°): 110

TECHNICAL DATA

Light Source: LED
Input Power (W): 37
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,95
Luminaire Luminous Flux (lm): 4561
Luminaire Efficacy (lm/W): 123
Unified Glare Rating (UGR): <25
LED Lifetime - Rated Median Useful Life: 72.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: B
LED Module Forward Voltage Range (VF): 11,5
Power Supply Dimming: DALI 2
Maximum of Luminaires by Magnetic Circuit Breaker B16: <21
Inrush Current (A): 29
Pulse Duration (µs): 155

DIMENSIONS

L - Length (mm): 1225
W - Width (mm): 300
H - Height (mm): 115
D - Recess Dimensions (mm): 1197x272
H - Recess Height (mm): 115
Net Weight (kg): 14