



ROFY 60 SQ L1342W286 GCONTROL+ DALI K3 830 1 LO
ARCHITECTURAL LIGHTING

90719L132H13300



Light distribution



L=1342mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted, Suspended, Wall mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

ROFY 60 SQ L1342W286 GCONTROL+ DALI K3 830 1 LO

CHARACTERISTICS

Luminaire Type: Rectangular luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 40
Mechanical Impact Protection (IK): 4
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Aluminium
Frame Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: Mist (1)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: gCONTROL+ - Microprismatic diffuser
Light Distribution: Direct
Beam Angle (°): 89

TECHNICAL DATA

Light Source: LED
Input Power (W): 42
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,96
Luminaire Luminous Flux (lm): 5098
Luminaire Efficacy (lm/W): 121
Emergency Unit: 3
Unified Glare Rating (UGR): <19
LED Lifetime - Rated Median Useful Life: 80.000h @ L90, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: C
LED Module Forward Voltage Range (VF): 142
Power Supply Dimming: DALI 2
Maximum of Luminaires by Magnetic Circuit Breaker B16: <28
Inrush Current (A): 24
Pulse Duration (µs): 194

DIMENSIONS

L - Length (mm): 1342
W - Width (mm): 286
H - Height (mm): 85

NOTES

• For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately.