




CORA L60W60 3 BOPTICS HF K3 830 B LO

TECHNICAL LIGHTING

90724Q360EB3300**Light distribution**

L=597mm

PRODUCT DESCRIPTION**Application Areas:** Offices, Education, Health and care**Mounting Type:** Suspended**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**CORA L60W60 3 BOPTICS HF K3 830 B LO****CHARACTERISTICS****Luminaire Type:** Square luminaire**Luminaire Module:** Individual**Insulation Class:** I**Ingress Protection (IP):** 20**Ambient Temperature Range (°C):**]5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back**MATERIALS****Body Material:** Steel sheet**Finishing:** Epoxy polyester powder coated**Colour:** Black (B)**Glow-wire Resistance (°C):** 650**OPTICAL SYSTEM****Optical System:** bOPTICS - Symmetric reflector**Light Distribution:** Direct**Beam Angle (°):** 44**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 18**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,9**Luminaire Luminous Flux (lm):** 2250**Luminaire Efficacy (lm/W):** 125**Emergency Unit:** 3**Unified Glare Rating (UGR):** <10**LED Lifetime - Rated Median Useful Life:** 80.000h @ L90, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 3000**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** C**LED Module Forward Voltage Range (VF):** 32,6**Power Supply Dimming:** ON/OFF**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <50**Inrush Current (A):** 21**Pulse Duration (µs):** 132**DIMENSIONS****L - Length (mm):** 597**W - Width (mm):** 597**H - Height (mm):** 30**Net Weight (kg):** 5.4**NOTES**

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.