



REBA 50 BOPTICS INT L0638 SPOT 2 DALI 930 W/W 20° HO
ALUMINIUM PROFILE SYSTEMS

90750L002HW0BW2



Light distribution



L=638mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted, Suspended
Control Gear Included: No

REBA 50 BOPTICS INT L0638 SPOT 2 DALI 930 W/W 20° HO

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 20
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: White (W)/White (W)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: PB - Shiny reflector
Light Distribution: Direct
Beam Angle (°): 19

TECHNICAL DATA

Light Source: LED
Input Power (W): 20

Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,91
Luminaire Luminous Flux (lm): 2295
Luminaire Efficacy (lm/W): 115
Unified Glare Rating (UGR): <25
LED Lifetime - Rated Median Useful Life: 86.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 3000
Photobiological safety according to IEC 62471: Not Available
Colour Rendering Index (CRI): >90
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: E
LED Module Forward Voltage Range (VF): 34,9
Power Supply Dimming: DALI 2
Central Battery Emergency Lighting System (VDC): 176-280
Maximum of Luminaires by Magnetic Circuit Breaker B16: <50
Inrush Current (A): 21
Pulse Duration (µs): 115

DIMENSIONS

L - Length (mm): 638
W - Width (mm): 46.5
H - Height (mm): 66.5

NOTES

- To complete the product it is necessary to order the inner profile separately;
- For suspended version it is necessary to order the suspension, the current supply cable and the ceiling rose. Please order separately.