



DYNA MINI /C D174 PM HF 940 W 90° HO
ARCHITECTURAL LIGHTING

90761L00HEW0A00



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Surface mounted

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

Input Power (W): 21

Input Driver Voltage: 220-240V-50/60Hz

Power Factor (λ): 0,84

Luminaire Luminous Flux (lm): 2125

Luminaire Efficacy (lm/W): 101

United Glare Rating (UGR): <25

LED Lifetime - Rated Median Useful Life: 50.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K): 4000

Colour Rendering Index (CRI): >90

Chromaticity Tolerance (MacAdam step): <3

This Product Contains a Light Source of Energy Efficiency Class: E

LED Module Forward Voltage Range (VF): 33,3

Power Supply Dimming: ON/OFF

Maximum of Luminaires by Magnetic Circuit Breaker B16: <90

Inrush Current (A): 4

Pulse Duration (µs): 60

DYNA MINI /C D174 PM HF 940 W 90° HO

CHARACTERISTICS

Luminaire Type: Round downlight

Luminaire Module: Individual

Insulation Class: I

Ingress Protection (IP): 20

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Aluminium

Finishing: Epoxy polyester powder coated

Colour: White (W)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: PM - Matte reflector

Light Distribution: Direct

Beam Angle (°): 85

TECHNICAL DATA

Light Source: LED

DIMENSIONS

H - Height (mm): 213

D - Diameter (mm): 174

Net Weight (kg): 1.9