



DYNA MINI /C D174 PM DALI 940 W 90° MO
ARCHITECTURAL LIGHTING

90761L00MHW0A00



Light distribution



PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Surface mounted
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

DYNA MINI /C D174 PM DALI 940 W 90° MO

CHARACTERISTICS

Luminaire Type: Round downlight
Luminaire Module: Individual
Insulation Class: I
Ingress Protection (IP): 20
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Aluminium
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: PM - Matte reflector
Light Distribution: Direct
Beam Angle (°): 85

TECHNICAL DATA

Light Source: LED

Input Power (W): 13
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,81
Luminaire Luminous Flux (lm): 1454
Luminaire Efficacy (lm/W): 112
Unified Glare Rating (UGR): <22
LED Lifetime - Rated Median Useful Life: 50.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Colour Rendering Index (CRI): >90
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: E
LED Module Forward Voltage Range (VF): 33,6
Power Supply Dimming: DALI 2
Maximum of Luminaires by Magnetic Circuit Breaker B16: <38
Inrush Current (A): 30
Pulse Duration (µs): 100

DIMENSIONS

H - Height (mm): 213
D - Diameter (mm): 174
Net Weight (kg): 1.9