



**PAS LINE L2870 ASYM DALI 3F K3 840 W HO**  
BATTENS AND TRACK SYSTEMS

**90777L010SW3000**



**Light distribution**



L=2870mm

**PRODUCT DESCRIPTION**

**Application Areas:** Public spaces, Retail  
**Mounting Type:** Suspended  
**Control Gear Included:** Yes  
**Control Gear:** LED driver 220-240VAC-50/60Hz

**PAS LINE L2870 ASYM DALI 3F K3 840 W HO**

**CHARACTERISTICS**

**Luminaire Type:** Rectangular luminaire  
**Luminaire Module:** Middle (MID)  
**Insulation Class:** I  
**Ingress Protection (IP):** 20  
**Ambient Temperature Range (°C):** ]5, 25[  
**Warranty (Years):** 5  
**Current Supply Cable Entry Point:** Back

**MATERIALS**

**Body Material:** Extruded aluminium profile  
**Finishing:** Epoxy polyester powder coated  
**Colour:** White (W)  
**Glow-wire Resistance (°C):** 650

**OPTICAL SYSTEM**

**Optical System:** Lens  
**Light Distribution:** Direct  
**Beam Angle (°):** 72

**TECHNICAL DATA**

**Light Source:** LED  
**Input Power (W):** 118

**Input Driver Voltage:** 220-240V-50/60Hz  
**Power Factor (λ):** 0,96  
**Luminaire Luminous Flux (lm):** 18473  
**Luminaire Efficacy (lm/W):** 157  
**Emergency Unit:** 3  
**Unified Glare Rating (UGR):** <25  
**LED Lifetime - Rated Median Useful Life:** 80.000h @ L80, B10, Ta 25°C  
**CCT - Correlated Colour Temperature (K):** 4000  
**Colour Rendering Index (CRI):** >80  
**Chromaticity Tolerance (MacAdam step):** <3  
**LED Module Forward Voltage Range (VF):** 30,6  
**Power Supply Dimming:** DALI 2  
**Maximum of luminaires by Magnetic Circuit Breaker B16:** <25  
**Inrush Current (A):** 37  
**Pulse Duration (µs):** 147

**DIMENSIONS**

**L - Length (mm):** 2870  
**W - Width (mm):** 63  
**H - Height (mm):** 73

**NOTES**

- For suspended version order the suspension. Please order separately;
- To complete the product it is necessary to order the start kit, through-wiring and body connector kit. Please order separately;
- In the L2870 mm lengths, only half of the luminaire is equipped with emergency unit;
- Dimensions do not include start kit. To complete the line add 1 mm to the length;
- The maximum line length with 1 single feed/power point is 30000 mm.