



AURA L600 LIGHT+ HF 830 B
ARCHITECTURAL LIGHTING

90825L060EB0300



Light distribution



L=600mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

Mounting Type: Wall mounted

Control Gear Included: Yes

Control Gear: LED driver 220-240VAC-50/60Hz

AURA L600 LIGHT+ HF 830 B

CHARACTERISTICS

Luminaire Type: Rectangular luminaire

Luminaire Module: Individual

Insulation Class: I

Ingress Protection (IP): 40

Ambient Temperature Range (°C):]-5, 25[

Warranty (Years): 5

Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Steel sheet

Finishing: Epoxy polyester powder coated

Colour: Black (B)

Glow-wire Resistance (°C): 650

OPTICAL SYSTEM

Optical System: LIGHT+ - Opal diffuser

Light Distribution: Indirect

Beam Angle (°): 111

TECHNICAL DATA

Input Power (W): 31

Power Factor (λ): 0,95

Luminaire Luminous Flux (lm): 3866

Luminaire Efficacy (lm/W): 125

LED Lifetime - Rated Median Useful Life [Indirect]: 80.000h @ L80, B10, Ta 25°C

CCT - Correlated Colour Temperature (K) [Indirect]: 3000

Colour Rendering Index (CRI) [Indirect]: >80

Chromaticity Tolerance (MacAdam step) [Indirect]: <3

This Product contains a Light Source of Energy Efficiency Class [Indirect]: C

Power Supply Dimming [Indirect]: ON/OFF

DIMENSIONS

L - Length (mm): 600

W - Width (mm): 100

H - Height (mm): 45