



REBA 50 LITE LINE L1200 BGLARE HF 840 W
ALUMINIUM PROFILE SYSTEMS

90885L012EW0000



Light distribution



L=1122mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Suspended
Control Gear Included: Yes
Control Gear: LED driver 220-240VAC-50/60Hz

REBA 50 LITE LINE L1200 BGLARE HF 840 W

CHARACTERISTICS

Luminaire Type: Straight line luminaire
Luminaire Module: Middle (MID)
Insulation Class: I
Ingress Protection (IP): 40
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

MATERIALS

Body Material: Extruded aluminium profile
Finishing: Epoxy polyester powder coated
Colour: White (W)
Glow-wire Resistance (°C): 850

OPTICAL SYSTEM

Optical System: bGLARE - Microprismatic diffuser
Light Distribution: Direct
Beam Angle (°): 85

TECHNICAL DATA

Light Source: LED

Input Power (W): 15
Input Driver Voltage: 220-240V-50/60Hz
Power Factor (λ): 0,94
Luminaire Luminous Flux (lm): 1742
Luminaire Efficacy (lm/W): 116
Unified Glare Rating (UGR): <22
LED Lifetime - Rated Median Useful Life: 80.000h @ L80, B10, Ta 25°C
CCT - Correlated Colour Temperature (K): 4000
Photobiological safety according to IEC 62471: Risk group 1 - Low-risk (RG1)
Colour Rendering Index (CRI): >80
Chromaticity Tolerance (MacAdam step): <3
This Product Contains a Light Source of Energy Efficiency Class: D
LED Module Forward Voltage Range (VF): 67,7
Power Supply Dimming: ON/OFF
Central Battery Emergency Lighting System (VDC): 176-280
Maximum of Luminaires by Magnetic Circuit Breaker B16: <45
Inrush Current (A): 18
Pulse Duration (µs): 160

DIMENSIONS

L - Length (mm): 1122
W - Width (mm): 51
H - Height (mm): 60
Net Weight (kg): 2

NOTES

- To complete the product it is necessary to order start kit, suspension kit and power supply kit separately;
- Dimensions do not include start kit. To complete the line add 6 mm to the length.