


REBA 50 LITE D/I LINE L1200 BLINE DALI 840 W

ALUMINIUM PROFILE SYSTEMS

90886L012HW0000**Light distribution**

L=1122mm

PRODUCT DESCRIPTION**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care**Mounting Type:** Suspended**Control Gear Included:** Yes**Control Gear:** LED driver 220-240VAC-50/60Hz**REBA 50 LITE D/I LINE L1200 BLINE DALI 840 W****CHARACTERISTICS****Luminaire Type:** Straight line luminaire**Luminaire Module:** Middle (MID)**Insulation Class:** I**Ingress Protection (IP):** 40**Ambient Temperature Range (°C):**]-5, 25[**Warranty (Years):** 5**Current Supply Cable Entry Point:** Back**MATERIALS****Body Material:** Extruded aluminium profile**Finishing:** Epoxy polyester powder coated**Colour:** White (W)**Glow-wire Resistance (°C):** 960**OPTICAL SYSTEM****Optical System:** bLINE - Opal diffuser**Light Distribution:** Direct / Indirect**Beam Angle (°):** 101**TECHNICAL DATA****Light Source:** LED**Input Power (W):** 33**Input Driver Voltage:** 220-240V-50/60Hz**Power Factor (λ):** 0,93**Luminaire Luminous Flux (lm):** 3550**Luminaire Efficacy (lm/W):** 108**Unified Glare Rating (UGR):** <22**LED Lifetime - Rated Median Useful Life:** 80.000h @ L80, B10, Ta 25°C**CCT - Correlated Colour Temperature (K):** 4000**Photobiological safety according to IEC 62471:** Risk group 1 - Low-risk (RG1)**Colour Rendering Index (CRI):** >80**Chromaticity Tolerance (MacAdam step):** <3**This Product Contains a Light Source of Energy Efficiency Class:** D**LED Module Forward Voltage Range (VF):** 67,7**Power Supply Dimming:** DALI 2**Central Battery Emergency Lighting System (VDC):** 180-280**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <45**Inrush Current (A):** 10**Pulse Duration (µs):** 50**DIMENSIONS****L - Length (mm):** 1122**W - Width (mm):** 51**H - Height (mm):** 60**Net Weight (kg):** 2.1**NOTES**

- The indirect light diffuser is included on the product;
- To complete the product it is necessary to order start kit, suspension kit and power supply kit separately;
- Dimensions do not include start kit. To complete the line add 6 mm to the length.