


**RECESSED CEILING ROSE T12 Q200 13W 09-52V 250MA DALI B**  
ARCHITECTURAL LIGHTING

**971820B**



L=200mm

**PRODUCT DESCRIPTION**

**Application Areas:** Offices, Hotels and residential, Public spaces, Retail, Education, Health and care

**Mounting Type:** Suspended

**Control Gear Included:** No

**H - Height (mm):** 48

**D - Recess Dimensions (mm):** 135x135

**H - Recess Height (mm):** 48

**RECESSED CEILING ROSE T12 Q200 13W 09-52V 250MA DALI B**

**CHARACTERISTICS**

**Insulation Class:** II

**Ingress Protection (IP):** 20

**Ambient Temperature Range (°C):** ]-5, 25[

**Warranty (Years):** 5

**Current Supply Cable Entry Point:** Back

**NOTES**

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

**MATERIALS**

**Body Material:** Die-cast aluminium

**Finishing:** Epoxy polyester powder coated

**Colour:** Black (B)

**TECHNICAL DATA**

**Input Power (W):** 13

**Input Driver Voltage:** 220-240V-50/60Hz

**Power Supply Dimming:** DALI 2

**Maximum of Luminaires by Magnetic Circuit Breaker B16:** <38

**Inrush Current (A):** 30

**Pulse Duration (µs):** 100

**DIMENSIONS**

**L - Length (mm):** 200

**W - Width (mm):** 200