



RECESSED CEILING ROSE T52 Q200 21W 10-42V 500MA HF W
ARCHITECTURAL LIGHTING

972012W



L=200mm

PRODUCT DESCRIPTION

Application Areas: Offices, Hotels and residential, Public spaces, Retail, Education, Health and care
Mounting Type: Suspended
Control Gear Included: No

H - Height (mm): 48
D - Recess Dimensions (mm): 135x135
H - Recess Height (mm): 48

RECESSED CEILING ROSE T52 Q200 21W 10-42V 500MA HF W

CHARACTERISTICS

Insulation Class: II
Ingress Protection (IP): 20
Ambient Temperature Range (°C):]-5, 25[
Warranty (Years): 5
Current Supply Cable Entry Point: Back

NOTES

- To complete the product it is necessary to order the suspension, the current supply cable and ceiling rose. Please order separately.

MATERIALS

Body Material: Die-cast aluminium
Finishing: Epoxy polyester powder coated
Colour: White (W)

TECHNICAL DATA

Input Power (W): 21
Input Driver Voltage: 220-240V-50/60Hz
Power Supply Dimming: ON/OFF
Maximum of Luminaires by Magnetic Circuit Breaker B16: <30
Inrush Current (A): 15
Pulse Duration (µs): 100

DIMENSIONS

L - Length (mm): 200
W - Width (mm): 200